

Produkt	Motor	Relativt energiforbrug	Energiforbrug år, kWh	Hydraulisk effektivitet	Belysningseffektivitet	Fedtfiler effektivitet	Lydniveau, dB(A)	Maks. ydeevne, m³/t
LOFTEMHÆTTER								
Eclipse XM								
	Indoor1	B	66,6	A	N/A	F	71	675
	Indoor8	C	126,4	C	N/A	F	69	790
	Outdoor2	C	94,5	B	N/A	F	71	691
	Outdoor9	B	79,2	A	N/A	F	69	846
Heaven XM								
	Indoor1	A	51,3	A	C	F	71	675
	Indoor8	B	79,2	B	C	F	69	691
	Outdoor2	C	111,1	C	C	F	71	790
	Outdoor9	A	55,8	A	A	F	69	846
WS955 Basic LXM/PXM/SXM								
	Indoor1	B	58,8 - 89,4 (Light)	A	D (Light version)	F	57	706
	Indoor8	B	91,5 - 122,2 (Light)	B	D (Light version)	F	64	767
	Outdoor2	B	75,5 - 106,1 (Light)	B	D (Light version)	F	51	708
	Outdoor9	B	83,8	A	A (Light version)	F	68	824
WS956 Basic LXM/PXM/SXM								
	Indoor1	B	58,8 - 89,4 (Light)	A	D (Light version)	F	57	706
	Indoor8	B	91,5 - 122,2 (Light)	B	D (Light version)	F	64	767
	Outdoor2	B	75,5 - 106,1 (Light)	B	D (Light version)	F	51	708
	Outdoor9	B	83,8	A	A	F	68	824
WS958 XM-2/ WS 958 WXM-2								
	Indoor1	B	63,1	B	B	F	55	670
	Indoor8	B	96,9	B	B	F	62	900
	Outdoor2	B	73,4	A	B	F	59	790
	Outdoor9	A	61,6	A	B	F	62	898
WS960 XM-2								
	Indoor1	B	83,3	B	E	F	65	681
	Indoor8	C	120,1	B	E	F	70	855
	Outdoor2	C	97,8	B	E	F	71	736
	Outdoor9	A	61,6	A	B	F	62	898
BORDEMHÆTTER								
WH78SQW								
	Indoor1							
	Indoor8							
	Indoor10-2							
	Indoor12							
	Outdoor2							
	Outdoor9							
Gap 90 Black								
	Indoor1	A	47,5	B	N/A	C	66	600
	Indoor8	C	100,7	C	N/A	D	68	596
	Indoor10-2	B	52,1	C	N/A	C	70	484
	Indoor12	B	73,6	C	N/A	C	71	577
	Indoor13	C	87,2	C	N/A	C	66	645
	Outdoor2	B	73,6	C	N/A	D	68	582
	Outdoor9	B	67,7	B	N/A	E	65	702
Between 52B								
	Indoor1	A	47,8	A	N/A	C	66	618
	Indoor8	C	100,7	C	N/A	D	68	596
	Indoor10-2	C	59,7	D	N/A	C	70	493
	Indoor12	B	67,5	B	N/A	C	71	642
	Indoor13	C	87,2	C	N/A	C	66	645
	Outdoor2	B	73,1	C	N/A	D	68	597
	Outdoor9	B	70,7	B	N/A	E	69	666
Sunrise Black								
	Indoor1	A	48,7	A	C	C	59	660
	Indoor8	C	109,4	C	C	C	64	775
	Indoor10-2	C	65,7	D	C	C	61	525
	Indoor12	C	79,7	C	C	E	71	576
	Outdoor2	B	75,3	B	C	C	62	665
	Outdoor9	B	77,8	A	C	E	75	816
WL60GL								
	Indoor2	B	51,7	A	E	E	69	636
	Indoor1	B	50,5	B	E	E	66	595
	Indoor8	C	106,9	C	E	E	70	622
	Indoor10-2	C	58,1	C	E	E	67	478
	Indoor12	B	73	B	E	E	67	540
	Outdoor2	C	88,9	C	E	E	68	577
	Outdoor9	B	71,4	B	A	E	70	680

Tekniske specifikationer

Emhætter med ekstern mortor

Produkt	Motor	Relativt energiforbrug	Energiforbrug år, kWh	Hydraulisk effektivitet	Belysningseffektivitet	Fedtfiler effektivitet	Lydniveau, dB(A)	Maks. ydeevne, m³/t
WL90GL-2								
	Intern2	A	51,1	A	E	E	68	757
	Indoor1	B	61,1	A	E	E	59	682
	Indoor8	C	109,2	B	E	F	64	753
	Indoor10-2	C	60,8	C	E	F	61	530
	Indoor12	B	71,7	A	E	E	68	668
	Outdoor2	C	89,5	C	E	E	62	731
	Outdoor9	B	81,1	A	A	E	75	816
WL120GL								
	Intern2	B	60,7	A	F	E	65	791
	Indoor1	B	58,7	A	F	E	55	736
	Indoor8	C	107,3	B	F	F	60	807
	Indoor10-2	C	67,1	C	F	E	59	559
	Indoor12	B	77,4	A	F	F	68	698
	Outdoor2	C	99,4	B	F	E	57	738
	Outdoor9	A	82,7	A	F	E	78	873
Glider 90 BW								
	Intern2	A	49,6	A	E	E	68	750
	Indoor1	B	51,7	A	E	E	59	687
	Indoor8	B	97,9	B	E	F	64	816
	Indoor10-2	C	57,2	C	E	E	61	530
	Indoor12	B	70,3	A	E	E	68	668
	Outdoor2	B	79,4	B	E	E	62	718
	Outdoor9	B	79,6	A	E	E	75	816
Push 90 BW								
	Intern2	B	56,9	B	F	E	68	681
	Indoor1	B	55,4	B	F	E	59	633
	Indoor8	C	104,7	B	F	F	64	753
	Indoor10-2	C	57,9	C	F	E	70	478
	Indoor12	C	79,7	C	F	E	71	576
	Outdoor2	C	80,2	C	F	E	62	639
	Outdoor9	B	76,5	A	F	E	75	816

VÆGEMHÆTTER								
WS75SX-3								
	Indoor1	B	61,6	A	B	D	72	697
	Indoor8	B	98,4	B	B	D	72	848
	Outdoor2	B	76,5	B	B	D	72	750
	Outdoor9	A	59,1	A	B	F	74	897
WS75BX/WX								
	Indoor1	B	61,6	A	B	D	72	697
	Indoor8	B	98,4	B	B	D	72	848
	Outdoor2	B	76,5	B	B	D	72	750
	Outdoor9	A	59,1	A	B	F	74	897

SKABSINTEGREREDE EMHÆTTER								
WS90370SEM-2								
	Indoor1	B	58,1	B	A	B	65	630
	Indoor8	C	99,4	C	A	B	62	707
	Outdoor2	C	80,2	C	A	B	66	630
	Outdoor9	A	56	A	A	F	71	869
WS90390SEM-2								
	Indoor1	B	58,5	B	A	B	65	624
	Indoor8	C	101,7	C	A	B	62	714
	Outdoor2	C	81,1	C	A	B	66	632
	Outdoor9	A	56	A	A	F	71	869
WS90752SEM-2								
	Indoor1	B	57,9	B	D	B	65	630
	Indoor8	C	99,1	C	D	B	71	707
	Outdoor2	C	79,9	C	D	B	66	630
	Outdoor9	B	64,9	A	D	F	68	826
WS90770SEM-2								
	Indoor1	B	74,3	B	F	B	65	624
	Indoor8	C	117,5	C	F	B	71	714
	Outdoor2	C	96,9	C	F	B	66	632
	Outdoor9	B	71,7	A	F	F	71	869